



Plastic Metal Unyka 55/195

Forza chiusura / Clamping force / Force de fermeture	ton	55
Passaggio colonne / Space between tie-bars / Distante entre les colonnes	mm	350 x 300
Spessore stampo / Mould thickness / Epaisseurs des moules (min-max)	mm	100 -350
Corsa piano mobile / Opening stroke / Course d'ouverture	mm	250
Corsa estrazione / Ejector stroke / Course éjection	mm	100
Diametro vite / Screw diameter / Diamètre de la vis	mm	35
Grammatura / Shot weight / Poids max injectable	gPs	132
Volume iniezione / Calculated injection / Volume d'injection	cm ³	140
Pressione specifica / Injection pressure / Pression d'injection	bar	1400
Potenza motore pompa / Motor pump power / Poissance du motor	kw	11
Potenza riscaldamento / Heating power / Poissance de chauffage	kw	6.3
Dimensioni (lu x la x h) / Dimension (le x wi x he) / Dimensions (lo x la x ha)	mt	3.4 x 1.1 x 1.8
Peso / Weight / Poids	kg	2500

I DATI POSSONO ESSERE SOGGETTO A MODIFICHE - DATA MAY BE SUBJECT TO ALTERATION - LES DONNÉES PEUVENT ÊTRE SUJETS À CHANGEMENT

PAR.COM. s.r.l.

Via Verga 74 10036 Settimo Torinese (Torino) Italia
+39 011 8977649 - +39 011 8977527
info@parcomsrl.it - www.parcomsrl.it